SURE RANGE Tray Sealers (manual range)

SURE RANGE Models TSM101-R, TSM102-R & TSM105-R

The SURE RANGE table top manual tray sealer range comprises of three models of different sizes. The manual operation is a very simple lever operation. The operator pushes the mould into the machine and pulling the lever down starts the sealing cycle. Once completed, the lever is released and the mould slid out. Various size moulds can be designed, including single and double moulds on the larger models. The TSM105-R can also seal trays up to ½ Gastronorm sizes. The unique and patented INFINITY mould system is easily adjustable to several tray sizes, this gives extra flexibility is use.

DESCRIPTION

Model Range

TSM101-R TSM102-R TSM105-R

SPECIFICATIONS

Finish

This machine is constructed mainly from stainless steel with aluminium

INFINITY 1 mould (tray sizes)

137x95 / 137x190 / 137x125mm

INFINITY 2 mould (tray sizes)

137x95 / 137x190 / 190x230 / 190x260mm

TSM101-R TSM102-R TSM105-R

INFINITY PLUS mould (tray sizes)

137 x 125 / 137x190 / 190x230 / 190x260 / 137x95 (x2) mm

Tray Size	Approvals		
TSM101-R; maximum 205 x 150 x 100mm (H) TSM102-R; maximum 260 x 195 x 155mm (H) TSM105-R; maximum 370 x 280 x 155mm (H)	CE Conformity: EC machine directive 98/37/EEC.		
Environment			
The machine should be cleaned at least once a day. High-pressure water and steam cleaning should NOT be used.	EC EMC directive 89/336/EEC. EC low voltage directive 73/23/EEC.		
Product Packed			
Fresh, frozen and chilled products			
Product Limitations			
The following products should not be processed in this machine: - Not applicable			



SURE RANGE Tray Sealers (manual range)

DIMENSIONS CHART				
	DIMENSIONS & TSM101-R	TSM102-R	TSM105-R	
	13H101-K	15H102-K	13H103-K	
Max tray dimension	205 x 150mm	260 x 195mm	370 x 280mm	
Max tray depth	100mm	155mm	155mm	
Max film dimensions	150mm (W) x 200 Metre (long)	200mm (W) x 200 Metre (long)	380mm (W) x 200 Metre (long)	
Overall machine dimensions $(W \times D \times H)$	260 x 390 x 500mm	315 x 450 x 555mm	485 x 510 x 555mm	
Net weigh	20kg	25kg	35kg	
	CDECTETCA	TTON		
SPECIFICATION TSM101-R TSM102-R TSM105-R				
	ISMIUI-K	15M102-K	1511105-K	
Working position	Table top	Table top	Table top	
Operation type	Manual	Manual	Manual	
Operational control	Electrical	Electrical	Electrical	
Number of programs	5	5	5	
Mould type:	,			
INFINITY 1	√	X	X	
INFINITY 2 INFINITY 1 DOUBLE	X	√	J	
INFINITY I DOUBLE INFINITY PLUS	X X	X J	J	
Single mould	<u>``</u>	J	J	
Multi-mould	X	J	J	
Die (profile) cut	X	X	X	
Seal type	Seal only	Seal only	Seal only	
Temperature control to sealing plate	0 – 200 °C		0 – 200 °C	
Cycles per minute	5 - 8	6 – 8	6 - 8	
Power supply	500 W	700 W	1400 W	
Electrical specification	230V 50Hz 1 phase	230V 50Hz 1 phase	230V 50Hz 1 phase	
OPTIONS:				
Gas wash (single / multi mould)	х	х	х	
Gas wash (for Infinity mould)	Х	x	×	
Film slitter / cutter	X	J	J	
Film micro puncher (film breath)	J	J	J	
	SHIPPING SPECI	FICATIONS		
	TSM101-R	TSM102-R	TSM105-R	
	1011201 10	1011202 10	1011200 10	
Length (cm)	65	65	65	
Width (cm)	55	55	55	
Height (cm)	45	55	75	
Gross Weight (kg)	22	29	39	