
Comparison Chart



At a glance bi-optic scanner specification

	Datalogic Magellan		NCR RealScan™ 740FX	Metrologic	
	8300	8400		MS2320	MS2420
Scan Pattern					
Scan lines	52	52	54	66	54
Scan rate	3900 lines / sec	5200 lines / sec	6300 lines / sec	6000 lines / sec	5400 lines / sec
Scan zone	360°	360°	360°	360°	360°
Sides read	5	5	5	6	5
Epos interface options:	IBM 46XX, RS232, OEM USB, Dual RS232 scanner scale		RS232 USB (NCR/PC & IBM) IBM RS485	RS232, Aux. RS232, IBM 468X/469X, USB, OCIA	
Power:	100-250 VAC, 50-60Hz 7 watts nominal, 4 watts while in stand by		12V terminal power option 90-264 VAC / 47-63 Hz 7 watts while scanning, 3 watts while in standby	5.2V / 12V 13.5 watts scanning, 5 watts standby	5.2V / 12V 13 watts scanning, 3.25 watts standby

© Avery Berkel 2009. All rights reserved. This publication is issued to provide outline information only which, unless agreed in writing by Avery Berkel, a division of ITW Limited, may not be regarded as a representation relating to the products or services concerned. Avery Berkel, a division of ITW Limited, reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.

Foundry Lane, Smethwick West Midlands, England B66 2LP

Tel: +44 (0)870 903 2000 Fax: +44 (0)870 904 2223 Email: info@averyberkel.com Internet: www.averyberkel.com







maximise productivity and efficiency

From low profile to horizontal and 360° bi-optic scanning, we have the checkout solution for you



FX132 / FX137

bi-optic 360° scanner scales



- Easy to integrate and available as a scale kit only or a complete scanner scale.
- Low power consumption the scale can be powered separately or from the scanner.
- RS232 or USB scale interface and a range of protocols including OPOS & JPOS for easy integration with ECR/EPoS.
- Column-mounted weight only or price computing displays.
- The NCR RealScan[™] 740FX scanner incorporates NCR's optical effects technology, which drives more scan lines at greater lengths to improve scan coverage and bar code read rates.
- The scanner can be powered by the EpoS / ECR, reducing cables and power consumption.
- Designed for ease of use, the NCR RealScan[™] 740FX has 5 LEDs to let the cashier know when it is ready for use and, when scanning is successful. It also offers audio feedback to assist in fault diagnosis.